

YAESU VX-2R QUICK REFERENCE

TX PWR:	[H/L]	LOCK:	[F/W]	[BAND]	1 SEC
CTCSS					
SET:	[F/W]	[MD]	DIAL	TONE "T" ICON	
	[H/L]	44:TN FRQ	DIAL: Hz	[H/L]	PTT
MEMORY					
STORE:	[F/W]	1 SEC	DIAL: CH#	[F/W]	
RECALL:	VFO MODE:		[V/M]	DIAL: CH#	
NAME:	[H/L]	NM SET	DIAL	ALP/NUM	[V/M]
		MISTAKE?:		[BAND]	
		FINISH:		PTT	
SHOW:	[H/L]	28:NAME	NAME	[H/L]	
			ALPHA	PTT	
MEMORY BANK					
ASSIGN:	[F/W]	1 SEC	DIAL	b1..b20	[F/W]
REMOVE:	[F/W]	1 SEC	[∞(SP BNK)ARTSTXPO]		
SCANNING					
	[BAND]	1 SEC	RELEASE [BAND] TO START		
SKIP:	[H/L]	39:SKIP	DIAL	SKIP	> STUDY
PREF:	[H/L]	39:SKIP	DIAL	ONLY	> BLINKS
PAUSE:	[H/L]	31:RESUME	DIAL	PAUSE	TIME
APO (AUTOMATIC POWER OFF)					
	[H/L]	1:APO	DIAL	ON TIME	PTT
PRI CH. SET:	"MEM." MODE	[F/W]	1 SEC	DIAL CH. #	
	[BAND]			"PRI" ICON	
DUAL WATCH:	[V/M]	1 SEC	CHKS "PRI" @5 S		
ATT:	[H/L]	5:ATT	ON/OFF	RX ATTENUATOR	